

# UNICARRIERS<sup>®</sup>

## □ FORKLIFT □



# Platinum II<sup>®</sup> Series

Engine Powered Forklifts


Gas, LP, Dual Fuel

3,000 - 7,000 lbs. Capacities | Pneumatic Tire



S P E C I F I C A T I O N S

DIMENSIONS



## MAIN TRUCK SPECIFICATIONS

CHARACTERISTICS	1		Manufacturer's Name		UniCarriers	UniCarriers	UniCarriers			
	2		Model		PF30	PF35	PFS40			
	3		Long Model Code		MP1F1A15JV / LV / DV	MP1F1A18JV / LV / DV	MP1F1A20JV / LV / DV			
CHARACTERISTICS	4		Rated Load Capacity		lb (kg)	3000 (1350)	3500 (1600)	4000 (1800)		
	5		Load Center		Distance	in (mm)	24 (600)	24 (600)	24 (600)	
	6		Power Type			G - LP - G/LP	G - LP - G/LP	G - LP - G/LP		
	7		Operator Orientation			Sit	Sit	Sit		
	DIMENSIONS	8		Tire Type		Front & rear	Pneumatic	Pneumatic	Pneumatic	
		9		Wheels		Number (x=driven) front/rear	2 x / 2	2 x / 2	2 x / 2	
		10		Mast		Maximum fork height	in (mm)	130 (3300)	130 (3300)	130 (3300)
11				Standard freelif	in (mm)	6.2 (160)	6.2 (160)	6.2 (160)		
12		Forks		Thickness & width	in (mm)	1.5 x 4 (40x100)	1.5 x 4 (40x100)	1.5 x 4 (40x100)		
13				Length	in (mm)	42 (1070)	42 (1070)	42 (1070)		
14		Tilt Angle		Standard mast - fwd/back	degree	6/12	6/12	6/12		
15		Overall Dimensions		Length (to face of forks)	in (mm)	89.0 (2260)	90.2 (2290)	91.3 (2320)		
16				Width (single/dual tires)	in (mm)	41.9 (1065) / 58.3 (1480)	41.9 (1065) / 58.3 (1480)	41.9 (1065) / 58.3 (1480)		
17				Mast lowered (OHL)	in (mm)	84.4 (2145)	84.4 (2145)	84.4 (2145)		
18				Mast extended with LBR	in (mm)	179.3 (4555)	179.3 (4555)	179.3 (4555)		
19				Height - top of OHG	in (mm)	83.3 (2115)	83.3 (2115)	83.3 (2115)		
20				Height - top of standard LBR	in (mm)	48 (1220)	48 (1220)	48 (1220)		
21				Width - standard carriage	in (mm)	36.2 (920)	36.2 (920)	36.2 (920)		
22		Grade Clearance		Ramp breakover angle	tan (%)	49	49	49		
23				Departure angle	tan (%)	39	37	35		
24				Approach angle	tan (%)	37	37	37		
25		Turning Radius		Minimum outside	in (mm)	76.2 (1935)	77.6 (1970)	79.1 (2010)		
26		Overhang		Front	in (mm)	15.7 (400)	15.7 (400)	15.7 (400)		
27				Rear	in (mm)	18.1 (460)	19.3 (490)	20.5 (520)		
28		Min Right Angle Stack		Add load length & clearance	in (mm)	91.9 (2335)	93.3 (2370)	94.9 (2410)		
PERFORMANCE		29		Speeds Maximum		Travel - forward or reverse	mph (kmh)	11.5 (18.5)	11.5 (18.5)	11.5 (18.5)
		30				Lift - full/empty	fpm (mm/sec)	122/127.9 (620/650)	122/127.9 (620/650)	122/127.9 (620/650)
		31				Lowering - full/empty	fpm (mm/sec)	98.4 (500)	98.4 (500)	98.4 (500)
		32		Drawbar Pull Max		Full load	lb (kg)	3705 (1680)	3705 (1680)	3705 (1680)
		33				Empty	lb (kg)	2470 (1120)	2646 (1200)	2932 (1330)
		34		Gradeability Max (1.2 mph)		Full/empty	tan (%)	31 / 28	38 / 24	33 / 21
WEIGHT		35		Truck Weight		Standard truck - no load	lb (kg)	5810 (2635)	6175 (2800)	6505 (2950)
	36		Weight Distribution		Front axle - empty	lb (kg)	2540 (1150)	2440 (1105)	2340 (1060)	
	37				Rear axle - empty	lb (kg)	3270 (1485)	3735 (1695)	4165 (1890)	
	38				Front axle - with rated load	lb (kg)	7710 (3620)	8475 (3985)	9235 (4350)	
	39				Rear axle - with rated load	lb (kg)	1100 (515)	1200 (565)	1270 (600)	
CHASSIS & WHEELS	40		Tire Size		Front - single (or dual) tire		6.50-10-10PR	6.50-10-10PR	6.50-10 Solid	
	41				Rear		5.00-8-8-PR	5.00-8-8-PR	5.00-8 Solid	
	42		Wheelbase			in (mm)	55.1 (1400)	55.1 (1400)	55.1 (1400)	
	43		Tread - Center of Tire		Front / rear	in (mm)	35/35.4 (890/900)	35/35.4 (890/900)	35/35.4 (890/900)	
	44				Front dual tires	in (mm)	43.1 (1095)	43.1 (1095)	43.1 (1095)	
	45		Headroom		SIP to bottom of OHG	in (mm)	42.5 (1080)	42.5 (1080)	42.5 (1080)	
	46		Counterweight Height			in (mm)	41.9 (1065)	41.9 (1065)	41.9 (1065)	
	47		Step Height			in (mm)	17.7 (450)	17.7 (450)	17.7 (450)	
	48		Ground Clearance		Under mast	in (mm)	4.5 (115)	4.5 (115)	4.5 (115)	
	49				Under power unit	in (mm)	5.3 (135)	5.3 (135)	5.3 (135)	
	50				Under frame (WB center)	in (mm)	5.9 (150)	5.9 (150)	5.9 (150)	
	51		Service Brake		Type		Drum and Shoe	Drum and Shoe	Drum and Shoe	
	52		Parking Brake		Type		Hand	Hand	Hand	
	53		Steering		Type		Full Hydraulic	Full Hydraulic	Full Hydraulic	
DRIVE LINE	54		Engine		Model		GK21	GK21	GK21	
	55		Rated Output		SAE gross	hp (kW) @ rpm	55 (41) @ 2700	55 (41) @ 2700	55 (41) @ 2700	
	56		Rated Torque		SAE gross	ft-lb (Nm) @ rpm	111.4 (151) @ 2000	111.4 (151) @ 2000	111.4 (151) @ 2000	
	57		Displacement			cu in (cm <sup>3</sup> )	126 (2065)	126 (2065)	126 (2065)	
	58		Transmission		Type		Automatic	Automatic	Automatic	
59				Number speeds - fwd/rev		1/1	1/1	1/1		

## MAIN TRUCK SPECIFICATIONS

CHARACTERISTICS	1	Manufacturer's Name		UniCarriers		
	2	Model	Model designation	PF40		
	3	Long Model Code		MP1F2A20JV / LV / DV		
DIMENSIONS	4	Rated Load Capacity	lb (kg)	4000 (1800)		
	5	Load Center	Distance	24 (600)		
	6	Power Type		G - LP - G/LP		
	7	Operator Orientation		Sit		
	8	Tire Type	Front & rear	Pneumatic		
	9	Wheels	Number (x=driven) front/rear	2 x / 2		
	10	Mast	Maximum fork height	in (mm)	130 (3300)	
	11		Standard freelif	in (mm)	6.1 (155)	
	12	Forks	Thickness & width	in (mm)	1.5 x 4 (40x100)	
	13		Length	in (mm)	42 (1070)	
	14	Tilt Angle	Standard mast - fwd/back	degree	6/12	
	15	Overall Dimensions	Length (to face of forks)	in (mm)	96.9 (2460)	
	16		Width (single/dual tires)	in (mm)	45.3 (1150) / 64.6 (1640)	
	17		Mast lowered (OHL)	in (mm)	84.4 (2145)	
	18		Mast extended with LBR	in (mm)	179.3 (4555)	
	19		Height - top of OHG	in (mm)	83.5 (2120)	
	20		Height - top of standard LBR	in (mm)	48 (1220)	
	21		Width - standard carriage	in (mm)	40.2 (1020)	
	22	Grade Clearance	Ramp breakover angle	tan (%)	44	
	23		Departure angle	tan (%)	45	
	24		Approach angle	tan (%)	32	
	25	Turning Radius	Minimum outside	in (mm)	83.5 (2120)	
	26	Overhang	Front	in (mm)	17.5 (445)	
	27		Rear	in (mm)	16.3 (415)	
28	Min Right Angle Stack	Add load length & clearance	in (mm)	101 (2565)		
PERFORMANCE	29	Speeds Maximum	Travel - forward or reverse	mph (kmh)	11.8 (19)	
	30		Lift - full/empty	fpm (mm/sec)	118.1/127.9(600/650)	
	31		Lowering - full/empty	fpm (mm/sec)	98.4 (500)	
	32	Drawbar Pull Max	Full load	lb (kg)	3880 (1760)	
	33		Empty	lb (kg)	3439 (1560)	
	34	Gradeability Max (1.2 mph)	Full/empty	tan (%)	31 / 28	
WEIGHT	35	Truck Weight	Standard truck - no load	lb (kg)	7145 (3240)	
	36	Weight Distribution	Front axle - empty	lb (kg)	3365 (1525)	
	37		Rear axle - empty	lb (kg)	3780 (1715)	
	38		Front axle - with rated load	lb (kg)	10015 (4709)	
	39		Rear axle - with rated load	lb (kg)	1130 (531)	
CHASSIS & WHEELS	40	Tire Size	Front - single (or dual) tire		7.00-12-12PR	
	41		Rear		6.00-9-10PR	
	42	Wheelbase		in (mm)	63 (1600)	
	43	Tread - Center of Tire	Front / rear	in (mm)	37.8/38.4 (960/975)	
	44		Front dual tires	in (mm)	47.4 (1205)	
	45	Headroom	SIP to bottom of OHG	in (mm)	42.5 (1080)	
	46	Counterweight Height		in (mm)	42.1 (1070)	
	47	Step Height		in (mm)	17.9 (455)	
	48	Ground Clearance	Under mast	in (mm)	4.5 (115)	
	49		Under power unit	in (mm)	5.3 (135)	
	50		Under frame (WB center)	in (mm)	6.1 (155)	
	51	Service Brake	Type		Drum and Shoe	
	52	Parking Brake	Type		Hand	
	53	Steering	Type		Full Hydraulic	
DRIVE LINE	54	Engine	Model		GK21	
	55	Rated Output	SAE gross	hp (kW) @ rpm	55 (41) @ 2700	
	56	Rated Torque	SAE gross	ft-lb (Nm) @ rpm	111.4 (151) @ 2000	
	57	Displacement		cu in (cm <sup>3</sup> )	126 (2065)	
	58	Transmission	Type		Automatic	
	59		Number speeds - fwd/rev		1/1	

## MAIN TRUCK SPECIFICATIONS

1	UniCarriers	UniCarriers	UniCarriers	UniCarriers	UniCarriers
2	PF50	PFU50	PF55	PF60	PF70
3	MP1F2A25JV / LV / DV	MU1F2A25JV / LV / DV	MUJ1F2A28JV / LV / DV	MUG1F2A30JV / LV / DV	MUG1F2A35JV / LV / DV
4	5000 (2250)	5000 (2250)	5500 (2500)	6000 (2700)	7000 (3150)
5	24 (600)	24 (600)	24 (600)	24 (600)	24 (600)
6	G - LP - G/LP	G - LP - G/LP	G - LP - G/LP	G - LP - G/LP	G - LP - G/LP
7	Sit	Sit	Sit	Sit	Sit
8	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
9	2 x / 2	2 x / 2	2 x / 2	2 x / 2	2 x / 2
10	130 (3300)	130 (3300)	130 (3300)	130 (3300)	130 (3300)
11	6.1 (155)	6.1 (155)	6.1 (155)	6.5 (165)	6.5 (165)
12	1.5 x 4 (40x100)	1.5 x 4 (40 x 100)	1.5 x 4 (40 x 100)	2 x 5 (50 x 125)	2 x 5 (50 x 125)
13	42 (1070)	42 (1070)	42 (1070)	42 (1070)	42 (1070)
14	6/12	6/12	6/12	6/12	6/12
15	99 (2515)	99 (2515)	102.8 (2610)	105.5 (2680)	108.5 (2755)
16	45.3 (1150) / 64.6 (1640)	45.3 (1150) / 64.6 (1640)	49.2 (1250) / 65.6 (1665)	49.2 (1250) / 65.6 (1665)	50.4 (1280) / 67.7 (1720)
17	84.4 (2145)	84.4 (2145)	85.6 (2175)	85.6 (2175)	91.1 (2315)
18	179.3 (4555)	179.3 (4555)	179.3 (4555)	179.4 (4560)	179.4 (4560)
19	83.5 (2120)	83.5 (2120)	84.6 (2150)	84.6 (2150)	84.8 (2155)
20	48 (1220)	48 (1220)	48 (1220)	48 (1220)	48 (1220)
21	40.2 (1020)	40.2 (1020)	40.2 (1020)	40.2 (1020)	40.2 (1020)
22	44	44	52	49	51
23	37	37	42	43	39
24	32	32	41	41	51
25	85.8 (2180)	85.8 (2180)	88.2 (2240)	90.6 (2300)	94.1 (2390)
26	17.5 (445)	17.5 (445)	18.5 (470)	18.9 (480)	19.3 (490)
27	18.5 (470)	18.5 (470)	20.5 (520)	19.7 (500)	22.2 (565)
28	103.3 (2625)	103.3 (2625)	106.7 (2710)	109.5 (2780)	113.4 (2880)
29	11.8 (19)	11.8 (19)	11.8 (19)	11.8 (19)	11.5 (18.5)
30	118.1/127.9 (600/650)	129.9/137.8 (660/700)	104.3/114.1 (530/580)	104.3/114.1 (530/580)	88.6/92.5 (450/470)
31	98.4 (500)	98.4 (500)	98.4 (500)	98.4 (500)	82.7/70.8 (420/360)
32	3880 (1760)	4189 (1900)	4189 (1900)	4189 (1900)	4034 (1830)
33	3439 (1560)	3439 (1560)	4057 (1840)	4167 (1890)	3968 (1800)
34	27 / 24	33 / 24	30 / 25	28 / 24	23 / 22
35	7925 (3595)	7925 (3595)	8825 (4000)	9265 (4200)	10120 (4590)
36	3200 (1450)	3200 (1450)	3395 (1540)	3825 (1735)	3760 (1705)
37	4725 (2145)	4725 (2145)	5430 (2460)	5440 (2465)	6360 (2885)
38	11515 (5430)	11515 (5430)	12590 (5935)	13700 (6460)	16215 (7240)
39	1410 (665)	1410 (665)	1735 (815)	1565 (740)	1905 (850)
40	7.00-12-12PR	7.00-12-12PR	28 x 9-15-12PR	28 x 9-15-12PR	250-15-16PR
41	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-12PR
42	63 (1600)	63 (1600)	63.8 (1620)	66.9 (1700)	66.9 (1700)
43	37.8/38.4 (960/975)	37.8/38.4 (960/975)	40.6/38.6 (1030/980)	40.6/38.6 (1030/980)	41.7/38.6 (1060/980)
44	47.4 (1205)	47.4 (1205)	47.6 (1210)	47.6 (1210)	48.4 (1230)
45	42.5 (1080)	42.5 (1080)	42.5 (1080)	42.5 (1080)	42.5 (1080)
46	42.1 (1070)	42.1 (1070)	43.3 (1100)	43.3 (1100)	43.5 (1105)
47	17.9 (455)	17.9 (455)	19.1 (485)	19.1 (485)	19.3 (490)
48	4.5 (115)	4.5 (115)	5.7 (145)	5.7 (145)	5.9 (150)
49	5.3 (135)	5.3 (135)	6.5 (165)	6.5 (165)	6.7 (170)
50	6.1 (155)	6.1 (155)	7.3 (185)	7.3 (185)	7.5 (190)
51	Drum and Shoe	Drum and Shoe	Drum and Shoe	Drum and Shoe	Drum and Shoe
52	Hand	Hand	Hand	Hand	Hand
53	Full Hydraulic	Full Hydraulic	Full Hydraulic	Full Hydraulic	Full Hydraulic
54	GK21	GK25	GK25	GK25	GK25
55	55 (41) @ 2700	62.9 (46.9) @ 2700	62.9 (46.9) @ 2700	62.9 (46.9) @ 2700	62.9 (46.9) @ 2700
56	111.4 (151) @ 2000	138.7 (188) @1600	138.7 (188) @ 1600	138.7 (188) @1600	138.7 (188) @ 1600
57	126 (2065)	151.8 (2488)	151.8 (2488)	151.8 (2488)	151.8 (2488)
58	Automatic	Automatic	Automatic	Automatic	Automatic
59	1/1	1/1	1/1	1/1	1/1

**MAST SPECIFICATIONS & RATED CAPACITIES**

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center					
						PF30		PF35		PFS40	
						Single Drive	Dual Drive	Single Drive	Dual Drive	Single Drive	Dual Drive
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)		lb (kg)		lb (kg)	
TWO STAGE (Wide view 2W)	2W270	106 (2700)	72.6 (1845)	6.2 (155)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2W300	118 (3000)	78.5 (1995)	6.2 (155)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2W330	130 (3300)	84.4 (2145)	6.2 (155)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2W350	138 (3500)	89.8 (2285)	6.2 (155)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2W370	146 (3700)	94.7 (2405)	6.2 (155)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2W400	157 (4000)	102.2 (2600)	6.2 (155)	6/6	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	3850 (1750)	3850 (1750)
	2W450	177 (4500)	112.0 (2845)	6.2 (155)	6/6	2900 (1300)	2900 (1300)	3200 (1450)	3200 (1450)	3450 (1550)	3750 (1700)
2W500	197 (5000)	121.9 (3100)	6.2 (155)	6/6	2650 (1200)	2800 (1250)	3100 (1400)	3100 (1400)	3200 (1450)	3300 (1500)	
TWO STAGE (Full free 2F)	2F300	118 (3000)	78.5 (1995)	53.6 (1360)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2F330	130 (3300)	84.4 (2145)	59.5 (1510)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2F350	138 (3500)	89.8 (2285)	64.8 (1645)	6/12	3000 (1350)	3000 (1350)	3500 (1600)	3500 (1600)	4000 (1800)	4000 (1800)
	2F370	146 (3700)	94.7 (2405)	69.8 (1770)	6/12	3000 (1350)	3000 (1350)	3400 (1550)	3450 (1550)	3900 (1750)	3950 (1800)
	2F400	157 (4000)	102.2 (2600)	77.2 (1960)	6/6	2900 (1300)	2900 (1300)	3300 (1500)	3350 (1500)	3800 (1700)	3850 (1750)
THREE STAGE (Full free 3F)	3F385	152 (3850)	72.6 (1845)	47.0 (1190)	6/6	2900 (1300)	2950 (1350)	3300 (1500)	3350 (1500)	3850 (1750)	3850 (1750)
	3F430	169 (4300)	78.5 (1995)	52.9 (1340)	6/6	2800 (1250)	2850 (1300)	3200 (1450)	3250 (1450)	3550 (1600)	3750 (1700)
	3F475	187 (4750)	84.4 (2145)	58.8 (1490)	6/6	2700 (1200)	2750 (1250)	3100 (1400)	3150 (1450)	3450 (1550)	3450 (1550)
	3F515	203 (5150)	89.8 (2285)	64.1 (1625)	6/6	2600 (1200)	2650 (1200)	2800 (1250)	2950 (1350)	3150 (1450)	3150 (1450)
	3F550	217 (5500)	94.7 (2405)	69.0 (1750)	6/6	2350 (1050)	2550 (1150)	2600 (1200)	2800 (1250)	2700 (1200)	2700 (1200)
	3F600	236 (6000)	102.2 (2600)	76.5 (1940)	6/6	1300 (600)	2150 (950)	1500 (700)	2300 (1050)	1800 (800)	2400 (1100)
	3F650	256 (6500)	112.0 (2845)	86.3 (2190)	6/6	1200 (550)	1500 (700)	1400 (650)	1500 (700)	1700 (750)	1750 (800)
	3F700	276 (7000)	121.9 (3100)	96.2 (2440)	6/6	1100 (500)	1300 (600)	1300 (600)	1400 (650)	1600 (750)	1650 (750)
THREE STAGE OPTVIEW® (3V)	3V360	142 (3600)	72.6 (1845)	48.4 (1225)	6/6	2900 (1300)	2900 (1300)	3300 (1500)	3350 (1500)	3700 (1700)	3700 (1700)
	3V405	159 (4050)	78.5 (1995)	54.3 (1375)	6/6	2800 (1250)	2800 (1250)	3200 (1450)	3250 (1450)	3550 (1600)	3550 (1600)
	3V450	177 (4500)	84.4 (2145)	60.2 (1525)	6/6	2700 (1200)	2700 (1200)	3100 (1400)	3150 (1450)	3450 (1550)	3450 (1550)
	3V490	193 (4900)	89.8 (2285)	65.5 (1660)	6/6	2600 (1200)	2600 (1200)	2800 (1250)	2900 (1300)	3150 (1450)	3150 (1450)
	3V525	207 (5250)	94.7 (2405)	70.4 (1785)	6/6	2350 (1050)	2500 (1150)	2600 (1200)	2700 (1200)	2700 (1200)	2700 (1200)
	3V575	226 (5750)	102.2 (2600)	77.9 (1975)	6/6	1300 (600)	2100 (950)	1500 (700)	1700 (750)	1800 (800)	2000 (900)
	3V633	249 (6330)	112.0 (2845)	87.8 (2230)	6/6	1200 (550)	1300 (600)	1400 (650)	1500 (700)	1700 (750)	1750 (800)

\*Without LBR

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center			
						PF40/PFU40			
						Single Drive		Dual Drive	
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)			
TWO STAGE (Wide view 2W)	2W270	106 (2700)	72.6 (1845)	6.1 (150)	6/12	4000 (1800)		4000 (1800)	
	2W300	118 (3000)	78.5 (1995)	6.1 (150)	6/12	4000 (1800)		4000 (1800)	
	2W330	130 (3300)	84.4 (2145)	6.1 (150)	6/12	4000 (1800)		4000 (1800)	
	2W350	138 (3500)	89.8 (2285)	6.1 (150)	6/12	4000 (1800)		4000 (1800)	
	2W370	146 (3700)	94.7 (2405)	6.1 (150)	6/12	4000 (1800)		4000 (1800)	
	2W400	157 (4000)	102.2 (2600)	6.1 (150)	6/6	4000 (1800)		4000 (1800)	
	2W450	177 (4500)	112.0 (2845)	6.1 (150)	6/6	3850 (1750)		3850 (1750)	
2W500	197 (5000)	121.9 (3100)	6.1 (150)	6/6	3450 (1550)		3700 (1700)		
TWO STAGE (Full free 2F)	2F300	118 (3000)	78.5 (1995)	53.5 (1355)	6/12	4000 (1800)		4000 (1800)	
	2F330	130 (3300)	84.4 (2145)	59.4 (1505)	6/12	4000 (1800)		4000 (1800)	
	2F350	138 (3500)	89.8 (2285)	64.7 (1640)	6/12	4000 (1800)		4000 (1800)	
	2F370	146 (3700)	94.7 (2405)	69.6 (1765)	6/12	4000 (1800)		4000 (1800)	
	2F400	157 (4000)	102.2 (2600)	77.1 (1955)	6/6	3950 (1800)		4000 (1800)	
THREE STAGE (Full free 3F)	3F385	152 (3850)	72.6 (1845)	47.2 (1195)	6/6	4000 (1800)		4000 (1800)	
	3F430	169 (4300)	78.5 (1995)	53.1 (1345)	6/6	3850 (1750)		3900 (1750)	
	3F475	187 (4750)	84.4 (2145)	59.0 (1495)	6/6	3700 (1700)		3750 (1700)	
	3F515	203 (5150)	89.8 (2285)	64.3 (1630)	6/6	3300 (1500)		3650 (1650)	
	3F550	217 (5500)	94.7 (2405)	69.2 (1755)	6/6	2950 (1350)		3550 (1600)	
	3F600	236 (6000)	102.2 (2600)	76.7 (1945)	6/6	1900 (850)		3400 (1550)	
	3F650	256 (6500)	112.0 (2845)	86.5 (2195)	6/6	1800 (800)		3250 (1450)	
	3F700	276 (7000)	121.9 (3100)	96.4 (2445)	6/6	700 (300)		2400 (1100)	
THREE STAGE OPTVIEW® (3V)	3V360	142 (3600)	72.8 (1850)	47.2 (1195)	6/6	3900 (1750)		3900 (1750)	
	3V405	159 (4050)	78.7 (2000)	53.1 (1345)	6/6	3700 (1700)		3750 (1700)	
	3V450	177 (4500)	84.6 (2150)	59.0 (1495)	6/6	3600 (1650)		3650 (1650)	
	3V490	193 (4900)	90.0 (2290)	64.3 (1630)	6/6	3300 (1500)		3400 (1550)	
	3V525	207 (5250)	94.9 (2415)	69.2 (1755)	6/6	3000 (1350)		3200 (1450)	
	3V575	226 (5750)	102.4 (2605)	76.7 (1945)	6/6	2500 (1150)		2900 (1300)	
	3V633	249 (6330)	112.2 (2850)	86.5 (2195)	6/6	2300 (1050)		2500 (1150)	
	3V688	271 (6880)	122.0 (3100)	96.4 (2445)	6/6	1900 (850)		2200 (1000)	

6 \*Without LBR

## STANDARD EQUIPMENT

### VEHICLE MANAGEMENT

- Vehicle Control Module (VCM)
- Operator security PIN access
- Interactive LCD meter panel
  - Hour meter, clock, calendar
  - On-board diagnostics
  - Programmable service reminders
  - Warning lights (oil pressure, transmission fluid, low coolant)
  - Speedometer & F/N/R transmission indicator
  - *LPM*ax low fuel warning (LP/Dual Fuel)
  - Fuel gauge
  - Water temperature gauge

### POWERTRAIN / FUEL SYSTEM

- GK21 & GK25 electronic fuel injected industrial engines
- Electronic engine control system
- Three-way catalytic converter
- Swing-out LP bracket<sup>1</sup>
- Maximum travel speed control

### BRAKE

- Parking brake with warning buzzer
- Parking brake with transmission interlock

### MAST / HYDRAULIC SYSTEM

- Seat-actuated auto-mast lock system
- High visibility carriage<sup>1</sup>
- Three-spool control valve with pressure relief

### OPERATOR CONVENIENCES

- Full suspension seat with weight & lumbar adjustment
- Overhead guard-mounted LED headlights
- Adjustable tilt steering wheel with memory lever

### PROTECTION / SECURITY

- Operator Presence System
  - Auto-mast lock
  - Return-to-neutral
  - Parking brake with warning buzzer
- Horn
- Back-up alarm
- Cushioned stability control
- Five-piece overhead guard

## OPTIONAL EQUIPMENT

- *SmoothShift* System
- Starter interlock (low LP)
- Travel speed control (high/low speed selector)<sup>2</sup>
- Controlled acceleration (power/economy selector)<sup>2</sup>
- Radiator screen
- Open core radiator
- Air intake pre-cleaner
- Diffusion exhaust muffler
- Swing-down LP bracket<sup>1</sup>
- OptiView three-stage mast
- Separate lift & tilt control levers (no charge)
- Electronic fingertip hydraulic controls (seat-mounted)<sup>1</sup>
- Automatic fork leveling<sup>1</sup>
- Sideshifters (integral or hang-on)
- Tilt cylinder boots & covers
- Bottler's tilt
- Rearview mirrors (glass or impact resistant)
- Rear LED combination light package (turn, stop, back-up)
- Reverse-activated rear LED drive light
- Secure rear grip with horn button<sup>1</sup>
- Seatbelt interlocks
- UL safety rating<sup>1</sup>
- Self-adjusting back-up alarm
- Fire extinguisher
- Strobe lights
- Rotating beacons
- Steering wheel with spinner knob

<sup>1</sup> Available on select models. Contact your UniCarriers dealer for details.

<sup>2</sup> Features can be combined. Available with rocker or key switch. Select 'Economy setting always on' for greatest fuel savings.

**MAST SPECIFICATIONS & RATED CAPACITIES**

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center	
						PF50/PFU50	
						Single Drive	Dual Drive
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)	
TWO STAGE (Wide view 2W)	2W270	106 (2700)	72.6 (1845)	6.1 (150)	6/12	5000 (2250)	5000 (2250)
	2W300	118 (3000)	78.5 (1995)	6.1 (150)	6/12	5000 (2250)	5000 (2250)
	2W330	130 (3300)	84.4 (2145)	6.1 (150)	6/12	5000 (2250)	5000 (2250)
	2W350	138 (3500)	89.8 (2285)	6.1 (150)	6/12	5000 (2250)	5000 (2250)
	2W370	146 (3700)	94.7 (2405)	6.1 (150)	6/12	5000 (2250)	5000 (2250)
	2W400	157 (4000)	102.2 (2600)	6.1 (150)	6/6	5000 (2250)	5000 (2250)
	2W450	177 (4500)	112.0 (2845)	6.1 (150)	6/6	4400 (2000)	4850 (2200)
	2W500	197 (5000)	121.9 (3100)	6.1 (150)	6/6	3700 (1700)	4650 (2100)
TWO STAGE (Full free 2F)	2F300	118 (3000)	78.5 (1995)	53.5 (1355)	6/12	5000 (2250)	5000 (2250)
	2F330	130 (3300)	84.4 (2145)	59.4 (1505)	6/12	5000 (2250)	5000 (2250)
	2F350	138 (3500)	89.8 (2285)	64.7 (1640)	6/12	5000 (2250)	5000 (2250)
	2F370	146 (3700)	94.7 (2405)	69.6 (1765)	6/12	5000 (2250)	5000 (2250)
	2F400	157 (4000)	102.2 (2600)	77.1 (1955)	6/6	4950 (2250)	5000 (2250)
THREE STAGE (Full free 3F)	3F385	152 (3850)	72.6 (1845)	47.2 (1195)	6/6	5000 (2250)	5000 (2250)
	3F430	169 (4300)	78.5 (1995)	53.1 (1345)	6/6	4700 (2150)	4900 (2200)
	3F475	187 (4750)	84.4 (2145)	59.0 (1495)	6/6	4300 (1950)	4750 (2150)
	3F515	203 (5150)	89.8 (2285)	64.3 (1630)	6/6	3650 (1650)	4600 (2100)
	3F550	217 (5500)	94.7 (2405)	69.2 (1755)	6/6	3350 (1500)	4450 (2000)
	3F600	236 (6000)	102.2 (2600)	76.7 (1945)	6/6	2100 (950)	4300 (1950)
	3F650	256 (6500)	112.0 (2845)	86.5 (2195)	6/6	2000 (900)	3850 (1750)
	3F700	276 (7000)	121.9 (3100)	96.4 (2445)	6/6	700 (300)	2600 (1200)
THREE STAGE OPTVIEW® (3V)	3V360	142 (3600)	72.8 (1850)	47.2 (1195)	6/6	4900 (2200)	4900 (2200)
	3V405	159 (4050)	78.7 (2000)	53.1 (1345)	6/6	4700 (2150)	4750 (2150)
	3V450	177 (4500)	84.6 (2145)	59.0 (1495)	6/6	4300 (1950)	4500 (2050)
	3V490	193 (4900)	90.0 (2290)	64.3 (1630)	6/6	3900 (1750)	4300 (1950)
	3V525	207 (5250)	94.9 (2415)	69.2 (1755)	6/6	3500 (1600)	4000 (1800)
	3V575	226 (5750)	102.4 (2605)	76.7 (1945)	6/6	3000 (1350)	3900 (1750)
	3V633	249 (6330)	112.2 (2850)	86.5 (2195)	6/6	2600 (1200)	3500 (1600)
	3V688	271 (6880)	122.0 (3100)	96.4 (2445)	6/6	2300 (1050)	2500 (1150)

\*Without LBR

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center	
						PF55	
						Single Drive	Dual Drive
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)	
TWO STAGE (Wide view 2W)	2W270	106 (2700)	73.8 (1875)	6.1 (150)	6/12	5500 (2500)	5500 (2500)
	2W300	118 (3000)	79.7 (2025)	6.1 (150)	6/12	5500 (2500)	5500 (2500)
	2W330	130 (3300)	85.6 (2175)	6.1 (150)	6/12	5500 (2500)	5500 (2500)
	2W350	138 (3500)	90.9 (2310)	6.1 (150)	6/12	5500 (2500)	5500 (2500)
	2W370	146 (3700)	95.9 (2440)	6.1 (150)	6/12	5500 (2500)	5500 (2500)
	2W400	157 (4000)	103.3 (2625)	6.1 (150)	6/6	5500 (2500)	5500 (2500)
	2W450	177 (4500)	113.2 (2880)	6.1 (150)	6/6	5300 (2400)	5300 (2400)
	2W500	197 (5000)	123.0 (3125)	6.1 (150)	6/6	4300 (1950)	5200 (2350)
TWO STAGE (Full free 2F)	2F300	118 (3000)	79.7 (2025)	53.8 (1365)	6/12	5500 (2500)	5500 (2500)
	2F330	130 (3300)	85.6 (2175)	59.7 (1515)	6/12	5500 (2500)	5500 (2500)
	2F350	138 (3500)	90.9 (2310)	65.1 (1650)	6/12	5500 (2500)	5500 (2500)
	2F370	146 (3700)	95.9 (2440)	70.0 (1775)	6/12	5500 (2500)	5500 (2500)
	2F400	157 (4000)	103.3 (2625)	77.5 (1965)	6/6	5500 (2500)	5500 (2500)
THREE STAGE (Full free 3F)	3F385	152 (3850)	79.7 (2025)	55.7 (1410)	6/6	5500 (2500)	5500 (2500)
	3F430	169 (4300)	85.6 (2175)	61.6 (1560)	6/6	5300 (2400)	5300 (2400)
	3F475	187 (4750)	90.9 (2310)	66.9 (1695)	6/6	5100 (2300)	5100 (2300)
	3F515	203 (5150)	95.9 (2440)	71.8 (1820)	6/6	4000 (1800)	4900 (2200)
	3F550	217 (5500)	103.3 (2625)	79.3 (2010)	6/6	3200 (1450)	4800 (2200)
	3F600	236 (6000)	113.2 (2880)	89.1 (2260)	6/6	2300 (1050)	4600 (2100)
	3F650	256 (6500)	123.0 (3125)	99.0 (2510)	6/6	1100 (500)	4100 (1850)
	3F700	276 (7000)	132.9 (3380)	108.8 (2760)	6/6	550 (250)	3000 (1350)
THREE STAGE OPTVIEW® (3V)	3V385	152 (3850)	79.7 (2025)	55.7 (1410)	6/6	5450 (2450)	5450 (2450)
	3V430	169 (4300)	85.6 (2175)	61.6 (1560)	6/6	5300 (2400)	5300 (2400)
	3V470	185 (4700)	90.9 (2310)	66.9 (1695)	6/6	5000 (2250)	5000 (2250)
	3V505	199 (5050)	95.9 (2440)	71.8 (1820)	6/6	3750 (1700)	4900 (2200)
	3V555	219 (5550)	103.3 (2625)	79.3 (2010)	6/6	2800 (1250)	4700 (2150)
	3V600	236 (6000)	113.2 (2880)	89.1 (2260)	6/6	1850 (850)	4500 (2050)
	3V650	256 (6500)	123.0 (3125)	99.0 (2510)	6/6	1200 (550)	4000 (1800)
	3V700	276 (7000)	132.9 (3380)	108.8 (2760)	6/6	650 (300)	3400 (1550)

\*Without LBR



## MAST SPECIFICATIONS & RATED CAPACITIES

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center	
						PF60	
						Single Drive	Dual Drive
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)	
TWO STAGE (Wide view 2W)	2W270	106 (2700)	73.8 (1875)	6.5 (165)	6/12	6000 (2700)	6000 (2700)
	2W300	118 (3000)	79.7 (2028)	6.5 (165)	6/12	6000 (2700)	6000 (2700)
	2W330	130 (3300)	85.6 (2175)	6.5 (165)	6/12	6000 (2700)	6000 (2700)
	2W350	138 (3500)	90.9 (2310)	6.5 (165)	6/12	6000 (2700)	6000 (2700)
	2W370	146 (3700)	95.9 (2440)	6.5 (165)	6/12	6000 (2700)	6000 (2700)
	2W400	157 (4000)	103.3 (2625)	6.5 (165)	6/6	6000 (2700)	6000 (2700)
	2W450	177 (4500)	113.2 (2880)	6.5 (165)	6/6	5600 (2550)	5900 (2700)
	2W500	197 (5000)	123.0 (3125)	6.5 (165)	6/6	5150 (2300)	5700 (2600)
TWO STAGE (Full free 2F)	2F300	118 (3000)	79.7 (2025)	53.4 (1355)	6/12	6000 (2700)	6000 (2700)
	2F330	130 (3300)	85.6 (2175)	59.3 (1505)	6/12	6000 (2700)	6000 (2700)
	2F350	138 (3500)	90.9 (2310)	64.6 (1635)	6/12	6000 (2700)	6000 (2700)
	2F370	146 (3700)	95.9 (2440)	70.0 (1775)	6/12	6000 (2700)	6000 (2700)
	2F400	157 (4000)	103.3 (2625)	77.0 (1955)	6/6	5950 (2700)	6000 (2700)
THREE STAGE (Full free 3F)	3F385	152 (3850)	79.7 (2028)	54.8 (1390)	6/6	6000 (2700)	6000 (2700)
	3F430	169 (4300)	85.6 (2175)	60.7 (1540)	6/6	5800 (2650)	5800 (2650)
	3F475	187 (4750)	90.9 (2310)	66.0 (1675)	6/6	5600 (2550)	5650 (2550)
	3F515	203 (5150)	95.9 (2440)	70.9 (1800)	6/6	4700 (2150)	5450 (2450)
	3F550	217 (5500)	103.3 (2625)	78.4 (1990)	6/6	3700 (1700)	5300 (2400)
	3F600	236 (6000)	113.2 (2880)	88.2 (2240)	6/6	2650 (1200)	5100 (2300)
	3F650	256 (6500)	123.0 (3125)	98.1 (2490)	6/6	1500 (700)	4550 (2050)
	3F700	276 (7000)	132.9 (3380)	107.9 (2740)	6/6	1000 (450)	3000 (1350)
THREE STAGE OPTIVIEW® (3V)	3V385	152 (3850)	79.7 (2028)	54.8 (1390)	6/6	5950 (2700)	5950 (2700)
	3V430	169 (4300)	85.6 (2175)	60.7 (1540)	6/6	5750 (2650)	5750 (2600)
	3V470	185 (4700)	90.9 (2310)	66.0 (1675)	6/6	5500 (2500)	5550 (2500)
	3V505	199 (5050)	95.9 (2440)	70.9 (1800)	6/6	4700 (2150)	5450 (2450)
	3V555	219 (5550)	103.3 (2625)	78.4 (1990)	6/6	3700 (1700)	5300 (2400)
	3V600	236 (6000)	113.2 (2880)	88.2 (2240)	6/6	2600 (1200)	5000 (2250)
	3V650	256 (6500)	123.0 (3125)	98.1 (2490)	6/6	1400 (650)	4500 (2050)
		3V700	276 (7000)	132.9 (3380)	107.9 (2740)	6/6	1000 (450)

\*Without LBR

Mast Name		Maximum Fork Height	Overall Height Lowered	Free Lift*	Tilt Angle Forward/Backward	Rated Capacity 24 in (600 mm) Load Center	
						PF70	
						Single Drive	Dual Drive
		in (mm)	in (mm)	in (mm)	degrees	lb (kg)	
TWO STAGE (Wide view 2W)	2W300	118 (3000)	85.8 (2180)	6.5 (165)	6/12	7000 (3150)	7000 (3150)
	2W330	130 (3300)	91.1 (2315)	6.5 (165)	6/12	7000 (3150)	7000 (3150)
	2W350	138 (3500)	96.1 (2445)	6.5 (165)	6/12	7000 (3150)	7000 (3150)
	2W370	146 (3700)	103.5 (2630)	6.5 (165)	6/12	7000 (3150)	7000 (3150)
	2W400	157 (4000)	113.4 (2885)	6.5 (165)	6/6	6900 (3100)	7000 (3150)
	2W450	177 (4500)	123.2 (3130)	6.5 (165)	6/6	6800 (3050)	6900 (3100)
		2W500	197 (5000)	133.1 (3385)	6.5 (165)	6/6	6600 (2950)
TWO STAGE (Full free 2F)	2F300	118 (3000)	85.8 (2180)	57 (1445)	6/12	7000 (3150)	7000 (3150)
	2F330	130 (3300)	91.1 (2315)	62 (1570)	6/12	7000 (3150)	7000 (3150)
	2F350	138 (3500)	96.1 (2445)	67 (1700)	6/12	7000 (3150)	7000 (3150)
	2F370	146 (3700)	103.5 (2630)	74 (1875)	6/12	7000 (3150)	7000 (3150)
	2F400	157 (4000)	113.4 (2885)	84 (2130)	6/6	6900 (3100)	7000 (3150)
THREE STAGE (Full free 3F)	3F355	140 (3550)	74.2 (1885)	43.5 (1100)	6/6	7000 (3150)	7000 (3150)
	3F400	157 (4000)	80.1 (2035)	49.4 (1250)	6/6	7000 (3150)	7000 (3150)
	3F445	175 (4450)	86.0 (2185)	55.4 (1405)	6/6	6800 (3050)	6800 (3050)
	3F485	191 (4850)	91.3 (2320)	60.7 (1540)	6/6	6600 (2950)	6600 (2950)
	3F520	205 (5200)	96.3 (2450)	65.6 (1665)	6/6	6300 (2800)	6400 (2850)
	3F570	224 (5700)	103.7 (2635)	73.1 (1855)	6/6	5300 (2400)	6000 (2700)
	3F620	244 (6200)	113.6 (2890)	82.9 (2105)	6/6	3500 (1600)	4000 (1800)
	3F670	264 (6700)	123.4 (3135)	92.8 (2355)	6/6	2500 (1150)	3000 (1350)
THREE STAGE OPTIVIEW® (3V)	3V385	152 (3850)	80.1 (2035)	49.4 (1250)	6/6	7000 (3150)	7000 (3150)
	3V430	169 (4300)	86.0 (2185)	55.4 (1405)	6/6	6900 (3100)	6900 (3100)
	3V470	185 (4700)	91.3 (2320)	60.7 (1540)	6/6	6700 (3000)	6700 (3000)
	3V505	199 (5050)	96.3 (2450)	65.6 (1665)	6/6	6500 (2900)	6500 (2900)
	3V555	219 (5550)	103.7 (2635)	73.1 (1855)	6/6	6200 (2800)	6300 (2800)
	3V600	236 (6000)	113.6 (2890)	82.9 (2105)	6/6	4400 (2000)	5000 (2250)
	3V650	256 (6500)	123.4 (3135)	92.8 (2355)	6/6	3200 (1450)	4500 (2050)
	3V700	276 (7000)	133.3 (3390)	102.6 (2605)	6/6	3000 (1350)	4000 (1800)

\*Without LBR

## ERGONOMICS & COMFORT

The Platinum II Series offers a variety of operator conveniences for greater productivity including standard full suspension seat for enhanced shock absorption. Seat includes lumbar support adjustment, weight-adjustment plus operator restraint armrests. Non-cinching seat belt provides greater range of movement. Adjustable tilt steering column includes memory lever. Operator Presence System has Return-to-Neutral and Auto-Mast Lock (automatically locking mast lift and tilt when the operator leaves the seat). Audible and visual warnings notify operator if seat belt is not engaged while traveling, or if parking brake is not applied before exiting truck. Floating powertrain includes four independent dampers to reduce vibrations that can cause operator fatigue.

Compact front cowl offers generous leg and foot room. Low profile design provides ample head clearance. Optional secure assist grip is mounted to the rear, right pillar, keeping the operator's hand safely inside the compartment during reverse travel. Can be purchased with an optional swivel seat\* that pivots 15° to left and right. [Reduces headroom by 1" (25mm)]. Hydrostatic power steering system reduces operator effort for easier maneuvering and less fatigue. Automotive-style levers simplify repetitive actions for greater operator focus. Exclusive single hydraulic control lever design combines lift and tilt operations into one fluid motion for greater productivity. Separate control levers available at no charge. Optional auto-tilt leveling system assists operator during mast/fork positioning. Optional fingertip control levers with adjustable armrest\* provide enhanced comfort.

## EFFICIENCY & CONTROL

Welded metal assist grip combined with replaceable metal traction plate bolted to a wide, low entry step, provide secure footing and grip for this often-repeated task. Small steering wheel delivers control and provides operator with clear view of meter panel with visibility to warnings and indicators.

Control of maximum travel speed is adjustable through the meter panel by a trained service technician. Optional Power/Economy controlled acceleration mode adjusts throttle sensitivity to increase fuel efficiency, extend drivetrain life and reduce excessive tire wear. An optional LP tank holder swings out 90°, then pulls down to a manageable height, requiring less force for simplified change out.

Maintenance-free cushioned stability control with rubber dampers located between rear axle and body enhance lateral stability under normal driving conditions.

\*Available on select models.

## LEGENDARY K-SERIES INDUSTRIAL ENGINES

Platinum II cushion tire models are powered by GCT GK21 (2.1 l) and GK25 (2.5 l) electronically controlled fuel injected industrial engines which include a bottom-bypass design with thermostat to eliminate hot spots during start up and prolong engine life. Designed and tested specifically for industrial applications, K21 and K25 engines deliver power and torque (in the low rpm range) more efficiently. An engine protection and warning system is standard, reducing speed in case of excessive heat generation or oil pressure loss. System includes three main components [Engine Control Module (ECM), Vehicle Control Module (VCM), and Multi-function LCD]. The ECM analyzes engine performance parameters and optimizes engine operation for enhanced productivity and lower fuel consumption. The ECM responds to sensor input by controlling basic engine-related functions (proper air/fuel ratio, torque and speed) based on application requirements. The VCM monitors sensors for changing conditions, alerting operator through warning indicators located on the meter panel. Communication among these components occurs through a Controller Area Network (CAN) system.

## LOW EMISSIONS

UCA's global commitment to preserving and protecting the environment is evident in our low emission engines. GK21/GK25 engines include a three-way catalytic muffler and an automotive-type, closed-loop design, providing cleaner exhaust emissions through lower CO (Carbon Monoxide) and combined HC+NOx (Greenhouse Gases) levels. Operators will experience low noise levels during idle and while driving at maximum travel speeds.

## LOWER OPERATING COSTS

No tools are required to remove the one-piece diamond tread floorboard, promoting fast, simple access to hydraulic and other serviceable components. Detachable side panels and a wide-open hood provide a roomy area for service technicians. Unique five-piece overhead guard simplifies replacement of individual components if necessary, saving time and money. An opening in the dash panel allows for fast brake fluid level checks. Multi-function LCD panel with on-board diagnostics reduces service time. Programmable service reminder settings keep periodic/planned maintenance on schedule.



UniCarriersAmericas.com

**SS-PLATINUM-II-PN 03-2018** Printed in U.S.A.

UniCarriers® is a registered trademark of UniCarriers Corporation. Platinum® and OptiView® are both registered trademarks of UniCarriers Americas. UniCarriers Americas Corporation reserves the right to make product changes relating to colors, equipment, specifications or available options without notice. For more information, contact your authorized UniCarriers representative.

# UNICARRIERS®

## □ FORKLIFT □



# Platinum II® Series

## Engine Powered Forklifts

Gas, LP, Dual Fuel

3,000 - 8,000 lbs. Capacities | Cushion Tire

3,000 - 7,000 lbs. Capacities | Pneumatic Tire



# Platinum II® Series Applications

Powered by our GTC K21 and K25 engines, the Platinum II sets the standard for performance, using less fuel and delivering more cycles per hour in a variety of demanding applications that include:

- Manufacturing
- Warehousing
- Recycling
- Beverage/Bottling
- Trucking



Look for these symbols for features available only on UniCarriers forklifts or that provide a proven performance advantage as compared to competitive trucks.



# NEVER QUIT.

It defines our forklifts and the company that builds them.

Over the course of a century, the company known as UniCarriers took shape. As we grew and evolved into a US manufacturer with a global reach in nearly 100 countries worldwide, much has changed, but one thing hasn't: our mission. UniCarriers is committed to providing you with the ultimate in reliability, performance, and value.

And that commitment can be seen in the Platinum II Series. Powered by our legendary K21 and K25 industrial engines, our rugged Platinum II forklifts deliver greater torque and horsepower...reduce CO, HC and NOx exhaust emissions...and come standard with some of the most advanced performance, security and operator comfort features available anywhere. Plus, it's all backed by the best standard, limited warranty in the business.



## Up Your UpTime

Discover reliability features that cut downtime and keep your business up and running



## Comfort Zone

Your drivers and your entire operation will benefit from our comfort & productivity features



## Power & Performance

You'll find amazing efficiency, reliability and performance in our K21 and K25 engines



## Sweet Savings

The Platinum II is designed to deliver you a low cost of ownership year after year after year



## Play It Safe

Safety is everybody's business, and the Platinum II is all business when it comes to safety



## Control Freak

You're in complete control when it comes to managing costs and productivity



## Versatility & Value

Discover how our unique design can help you improve performance indoors and out



## Make It Yours

Already well appointed, Platinum II can be customized to meet your specific needs



To learn more, and find a dealer near you, visit [UniCarriersAmericas.com](http://UniCarriersAmericas.com)



# Up Your UpTime

When it comes to keeping your operation up and running, the Platinum II Series offers you significant advantages, beginning with a reliable cooling design, service reminders and longer maintenance intervals. Throughout the Platinum II you'll find innovative and proven protection and warning systems to help you maximize uptime, while minimizing cost.

Trained technicians can **program service interval alerts** for each unit in operation through the meter panel. Drivers are notified when scheduled maintenance is required.

## Longer Preventative Maintenance Intervals

With the Platinum II Series, most major service intervals are only required every 500-600 hours, reducing labor and lowering your operating costs.

up to 600 hours



The Platinum II's display includes **standard warnings** like an **air cleaner light (if clogging occurs)** and **low coolant level**. You'll find common sense features like these as standard equipment on our forklifts – but not on our competitors'.



A standard **parking brake transmission interlock** keeps the forklift in neutral and prevents the operator from driving while the parking brake is engaged to protect the brakes and transmission and reduce premature brake wear.



Inhibit operators from shifting at high speeds with our **SmoothShift** system. This option limits transmission shock and excessive wear— and extends service life too.

## Easy LP Tank Changes

With our simplified LP replacement system, an optional bracket swings out 90°, then pulls down to a manageable height for faster, easier tank replacement. *Not available on all models.*



Keep your starter and battery healthy with a **starter interlock**. This optional equipment **protects the forklift's starting system** by restricting repeated attempts to start the engine when the LP system is out of fuel.

**Defend Against Overheating**

Our reliable cooling system includes an electronic engine protection and warning system that **monitors radiator fluid and transmission oil temperatures at all times**. This system also contains a field-proven bottom bypass design with thermostat to **prevent hot spots and prolong engine life**. And its large 10-blade fan and aluminum radiator produce effective cross-flow cooling.


## Reduce Downtime through Self-Diagnostics

Integrated **on-board diagnostics** provides immediate truck status. Standard equipment on the Platinum II Series, this intuitive dialogue display, combined with accessible service history, **reduces troubleshooting time**, so the unit is back in operation faster. Everything is done through its smart LCD panel. No handset device is needed.






# Comfort Zone



## Superior Visibility

A standard high-visibility carriage\* and your choice of an OptiView®, triple stage or wide-view mast — together these features produce clear sightlines for both loading and moving.

*\*Available at no additional cost on model capacities up to 5500 lbs.*



## Our Seat Supports Your Driver and Your Productivity

The lumbar support and weight adjustments create customized comfort for the operator, while a non-cinching seatbelt allows a wider range of movement. The full suspension design absorbs shocks for a smoother, more comfortable ride — and it's all standard on Platinum II Series forklifts.

**Lumbar support adjustment**

**Weight adjustment**

*Seat and backrest cushions can be individually replaced for enhanced savings.*





### Improved Control and Security

Maneuverability during reverse driving is easier with an optional secure assist grip. And it helps keep the operator's hand inside the compartment where it belongs. A horn button is included.



### Convenience at Your Fingertips

Standard automotive-style controls are located on either side of the steering column for accessibility and intuitive operation.



### Get a Smoother Ride


Pneumatic tire models are designed with a floating powertrain that includes four independent dampers, to reduce vibrations that can cause operator fatigue.

### *Better Fork Tip Visibility*

Controls are ergonomically placed across a low profile cowl, making visibility while picking up loads easier for a variety of operator heights.

### *Add a Spinner Knob for Easier Handling*

Operators love this optional feature because it gives them even easier control behind the wheel.





# Power & Performance

## Operator Efficiency Achieved

Choose the optional integral side shifter resulting in fewer moves to store and retrieve loads, while minimizing capacity loss versus hang-on designs.



## More Power, More Efficiently

Advanced engine technology makes it possible for our K21 and K25 engines to deliver **greater torque at lower RPMs**. This is achieved due to a combination of factors, including **direct ignition coils connected to each cylinder**, a centrally positioned spark plug on the combustion chamber as well as electronic monitoring and control systems. Platinum II models also include an atmospheric sensor that delivers enhanced performance in high altitudes.




## Paired for Maximum Performance

Built to our specifications, the Platinum II's transmission is uniquely designed to **optimize the horsepower and torque of our K21 and K25 industrial engines**. This proven drivetrain delivers powerful, yet efficient performance.

The Platinum II's standard Power setting allows you to achieve maximum performance — and an annual productivity increase of up to 2500 cycles per truck.

*Study findings are based on a 1200-hour usage*



## Cleaner Running Engines for Greater Performance



The injector valve's powerful opening force aids in conditions where lower quality LP fuel is used. Gas is located under the valve to **help reduce possible tar build up on the injectors** which can adversely affect performance. A pressure sensor is located between the two injectors.

## Consistent Performance through Reliable Technology

The Platinum II's engine and vehicle control modules along with multi-function display communicate through a reliable CAN-bus network to manage changing system requirements and maintain consistent performance.



## Built for Rugged Dependability

Solid steer axles and thick steel front fenders provide protection against harsh work environments.


Switch to the Platinum II's optional Economy mode to get greater fuel efficiency. Independent testing has shown our K21 engines use nearly 11% less fuel compared to competitive models under unloaded conditions.\*

\* Results based on 5000 lb. capacity LP cushion tire models in Economy mode.



### Compact Design

A small steering wheel and intuitive controls make these trucks highly suited for maneuverable performance within confined areas of the warehouse.





# Sweet Savings



## Reduce Tire Wear & Save Fuel

Our power/economy controlled acceleration feature restricts the acceleration rate to **maximize fuel economy and minimize tire spin**. Gradual acceleration is also **useful when moving fragile loads or operating in confined areas**. Three design choices for this option offer increasingly more **security against tampering**: toggle switch, key switch or set internal parameters to keep this feature activated.

## Extra Protection Without Extra Expense



In the event of excessive heat or loss in engine oil pressure, our **Powertrain Protection System** reduces engine RPM for longer engine and drivetrain life. This great feature is standard on models powered by our K21 and K25 engines, versus competitive forklifts requiring a costly add-on.



## Long Life LEDs

Everything about the Platinum II is designed for longer life and greater savings, including the standard LED headlights that deliver greater visibility while being more economical and cost-effective over the life of the machine.

**Repositionable Headlights**



## Save More, Waste Less


With the Platinum II's **standard LPM<sub>ax</sub> System** nearly every drop of liquid LP is used thanks to its reliable and timely low fuel warning, **reducing early tank replacement and saving you money**. An average 8-minute\* warning means the operator can maximize productivity — instead of lugging an empty tank to the refill station.



## Our Overhead Guard Reduces Your Overhead

Beyond ample headroom, the five-piece overhead guard takes **75% less time to make needed replacements** versus competitors' single-piece, welded-on guards. That cuts downtime and costs.

\*Based on typical traveling operation in unloaded condition. Time interval varies depending upon individual application and usage.



## Extended Service Intervals

The electronic ignition system means you'll service the Platinum II less often because the recommended times between routine maintenance is longer. And you'll spend less time doing it because the critical service points — including fluids, filters and belts — are all readily accessible.

## Eliminate Spark Plug Wires and Timing Adjustments

The engine cylinder timing is individually controlled through an ignition coil at each plug, eliminating associated maintenance. Free from mechanical linkages or aging wires that can cause performance loss, this design delivers better engine efficiency.

### Other serviceability features:

- *Easy oil filter replacement*
- *Fast fan belt adjustment*
- *Accessible radiator*



# Play It Safe

As a leader in clean air engines for nearly a decade, our products have benefited from the knowledge gained through our automotive heritage. Our K21 and K25 industrial engines incorporate an electronic engine control system, using a closed loop design to produce high combustion efficiency with lower and cleaner emission levels. We've also included several security systems as standard, and more options to meet your particular needs.



## For Even Greater Security

Several options are available for added protection:

- **Seatbelt Interlocks** include a variety of choices for restricting forklift operations if the seatbelt is not latched.
- **Fire Extinguisher** mounted to the overhead guard pillar, for quick and easy access.
- **Orange Seatbelt** is highly visible, making seatbelt usage easier to enforce.
- **LP Safety Rating** is UL approved.


## Operator Presence System



This comprehensive system includes a **seat-actuated power interrupt with mast-lock**, automatically preventing lift and tilt operations if the operator leaves the seat. The **return-to-neutral** feature minimizes forklift movement if the operator leaves the truck while still in gear. Other audible and visual warnings come standard, including **parking brake warning** and **seatbelt alarm**.



A rubber damper provides enhanced stability and easier handling



## Safety Doesn't Have to be Complicated

Unlike the complex systems offered by some competitors, our cushioned stability control is simple, extremely effective and **zero maintenance** — enhanced lateral stability is achieved by a rubber damper placed between the axle and frame.

## Seeing is Believing

Cylinders are positioned behind the mast rails resulting in fewer visual obstructions for the operator. Ideal for facilities that transport delicate loads, our optional OptiView<sup>®</sup> mast makes fork positioning and load handling easier.




OSHA strictly regulates carbon monoxide (CO) levels in the workplace for good reason.



The Platinum II's CO levels are among the lowest in its engine class — three times lower than those of a major competitor based on 2015 certification results from the California Air Resources Board.

We achieved these lower and cleaner emission levels through the higher combustion efficiency delivered by our electronic engine control system that incorporates a Vehicle Control Module (VCM), Engine Control Module (ECM) and a 3-way catalytic muffler.



\*Based on 2015 CARB certification results.



# Control Freak

## Make a Positive Impact

A variety of optional impact sensors are available to record each time the forklift comes into contact with a stationary object, allowing you to respond accordingly.



### Single Handle Control Lever

Faster, easier and more fluid, our single handle control **combines both lift and tilt functions for greater productivity**. It's standard equipment on the Platinum II Series — and not available from any other forklift brand. Separate control levers are available at no charge.



### Auto-Tilt Leveling System

Press the button on the hydraulic control lever to tilt the forks forward to a horizontal position. This option is used for easier load placement and retrieval operations.



### Parking Brake Alarm

As part of the Operator Presence System, a warning buzzer alerts the driver if he leaves the seat without first setting the parking brake.

### Forward Thinking ..... Back-Up Alarm

Our standard back-up alarm provides plenty of notice to pedestrians and other drivers in the area. For applications with varying noise levels, there is an optional self-adjusting alarm that adjusts sound volume based on ambient noise levels.





### Find Your Top Travel Speed Easier



With an optional speed switch, drivers can **toggle from a high speed pre-set in one area then select a low speed**, confident they are adhering to corporate requirements\*.



Select the security key switch option to **lock in a pre-set high or low speed\***.


### Set Travel Speeds Without Losing Productivity

Top travel speed is electronically controlled, so you won't sacrifice lift performance. The great news? No tools are needed to set desired speeds\*.

*\* Speed pre-sets performed by trained service technician*

### The Ultimate in Control

The interactive meter panel on the Platinum II Series provides operators and technicians with a wealth of information through its LCD warnings and readouts. A visual indicator for its return-to-neutral feature shows the forklift's transmission direction.



Our multi-function display provides an at-a-glance view of critical functions:

- A** Multipurpose warning
- B** Check engine warning
- C** Oil pressure warning
- D** Charge warning
- E** Parking brake warning
- F** Seatbelt warning
- G** Directional indicator
- H** Fuel & water temperature gauges
- I** Multi-function display:
  - Hour meter
  - Clock/calendar
  - Speedometer
  - Programmable service reminder
  - Error codes



# Versatility and Value

# The Nomad Series



## Two Forklifts in One

The Nomad Series is a UniCarriers exclusive. At home anywhere, its cushion tire-sized chassis rides on solid pneumatic tires to deliver exceptional performance both indoors and out. And because our Nomad is part of the Platinum II family, you'll also enjoy the same reliability that comes with utilizing UniCarriers brand equipment in your operation.

## For Indoor and Outdoor Use

The Nomad Series is available in 3000, 3500 and 5000 lb. lifting capacities. Its short wheelbase and tight turning radius mean it's sized like a standard cushion tire forklift, offering precise maneuverability in confined areas. But don't let its size fool you. It's just as effective in tough outdoor applications. And it offers higher capacity retention versus comparable pneumatic tire trucks.

*Operate on improved surfaces for best outdoor performance results.*



Don't downsize your fleet – right size it. A proven performer across a variety of applications, the Nomad is bound to be one of the most relied upon forklifts in your facility. From loading dock to work yard, you'll discover the many ways these flexible trucks will benefit your operation.



*\*Calculations based on comparison of Nomad vs. pneumatic tire forklift of same capacity.*



Get up to 8% tighter turning radius without sacrificing capacity.\*

**72.6-87.5**  
INCHES



# Make It Yours

Choose from a variety of options to customize your ride. If you don't see what you need, contact your authorized UniCarriers dealer for help.



Strobe & LED Work Lights



• Trucker's Mast

• High Air Intake Pre-Cleaner



• Overhead Guard-Mounted Fire Extinguisher



• Forks with High Visibility Paint



• Dual Drive Tires\*

\* Available on pneumatic tire models only. Standard, pre-drilled holes in thick front fenders simplify field installation of dual tire option. Data plate change is required. Consult factory.



**Debris Resistance Package**

Includes a belly screen and slotted wheel well inserts to prevent larger debris from entering the engine compartment and affecting key components. For additional protection, select the Recycler Package.



**Blue LED Pedestrian Awareness Light**

Reverse driving actuates an optional blue spotlight to illuminate the floor, for advanced visual warning.



**Tilt Cylinder Protection**

Cylinder boots and covers provide extra protection against contaminants that can cause premature wear on cylinder packing.



**Extended Overhead Guard**

Extension provides protection to mounted components, including on-board computer and headlight (shown).




**Fingertip Controls**

Increase operator productivity with ergonomic hydraulic controls. Choose single joystick or multiple lever designs.



**Polycarbonate Overhead Guard Cover**

Prevents small debris from entering the operator compartment through the overhead guard.



**Sidsifting Fork Positioner**

Hydraulically positions forks, eliminating the need for manual adjustment by the operator, providing increased productivity.



**Rear LED Combination Lights**

Package includes a reflector, turn signals, brake and back-up lights. Design provides high visibility and vibration resistance for long life and low service costs. Choose vertical or horizontal mounting (shown).



**Radiator Screen**

Minimizes debris entering radiator, resulting in more efficient engine cooling.

# Option Availability

● Standard ○ Optional

	LP	GASOLINE	DUAL FUEL
<b>VEHICLE MANAGEMENT</b>			
Vehicle Control Module (VCM)	●	●	●
Operator security PIN access	●	●	●
Interactive LCD meter panel	●	●	●
On-board diagnostics and programmable service reminders	●	●	●
Engine coolant temperature gauge	●	●	●
Oil pressure, transmission fluid and low coolant warning lights	●	●	●
LPM <sub>Max</sub> low fuel warning	●	–	●
Fuel gauge - gas	–	●	●
SmoothShift system	○	○	○
Starter interlock - low LP	○	–	○
<b>POWERTRAIN</b>			
Electronic Engine Control System	●	●	●
Engine/transmission protection and warning system	●	●	●
Floating powertrain for reduced vibration (pneumatic)	●	●	●
Three-way catalytic converter	●	●	●
Cushioned stability control	●	●	●
Travel speed control (high/low speed selector)	○	○	○
Controlled acceleration (power/economy selector)	○	○	○
Radiator screen	○	○	○
Diffusion exhaust muffler	○	○	○
<b>LP SYSTEM</b>			
Swing-out LP bracket*	●	–	●
Swing-down LP bracket*	○	–	○
<b>BRAKE</b>			
Parking brake with warning buzzer	●	●	●
Parking brake transmission interlock	●	●	●
<b>MAST</b>			
Seat actuated auto-mast lock system	●	●	●
OptiView® three-stage mast	○	○	○
High-Visibility Carriage*	●	●	●
<b>HYDRAULIC SYSTEM</b>			
Single lift/tilt control lever	●	●	●
Separate lift & tilt control levers	○	○	○
Automatic fork leveling*	○	○	○
<b>OPERATOR CONVENIENCES</b>			
Full suspension seat with weight & lumbar adjustment	●	●	●
Overhead guard-mounted LED headlights	●	●	●
Rearview mirrors	○	○	○
Rear LED combination light package (turn, stop, back-up)	○	○	○
Rear LED drive light	○	○	○
Secure rear grip with horn button	○	○	○
<b>PROTECTION /SECURITY</b>			
Operator Presence System with return-to-neutral and auto mast lock	●	●	●
Seatbelt interlocks	○	○	○
UL Safety rating*	○	–	–
Back-up warning alarm	●	●	●
Self-adjusting back up alarm	○	○	○
Fire Extinguisher	○	○	○

\*Available on select models. Consult factory.

# Specifications

Safety ratings available on select models/fuel types

## PNEUMATIC TIRE 3000 – 7000 LB. MODELS

SHORT MODEL CODES	PF30 PF30LP PF30DF	PF35 PF35LP PF35DF	PFS40 PFS40LP PFS40DF	PF(U)40 PF(U)40LP PF(U)40DF	PF(U)50 PF(U)50LP PF(U)50DF	PF55 PF55LP PF55DF	PF60 PF60LP PF60DF	PF70 PF70LP PF70DF
Engine Models Available	K21	K21	K21	K21/K25	K21/K25	K25	K25	K25
Load Capacity - lb	3000	3500	4000	4000	5000	5500	6000	7000
Wheelbase - in	55.1	55.1	55.1	63.0	63.0	63.8	66.9	66.9
Overall Width - in	41.9	41.9	41.9	45.3	45.3	49.2	49.2	50.4
Overall Length (no forks) - in	89.0	90.2	91.3	96.9	99.0	102.8	105.5	108.5
Overall Height (OHG) - in	83.3	83.3	83.3	83.5	83.5	84.6	84.6	84.8
Turning Radius (outside) - in	76.2	77.6	79.1	83.5	85.8	88.2	90.6	94.1

## CUSHION TIRE 3000 – 8000 LB. MODELS

SHORT MODEL CODES	CF30LP CF30DF	CF35LP CF35DF	CFS40LP CFS40DF	CF40 CF(U)40LP CF(U)40DF	CF50 CF(U)50LP CF(U)50DF	CF55 CF(U)55LP CF(U)55DF	CFS60LP CFS60DF	CF60LP CF60DF	CFS65LP CFS65DF	CF70LP CF70DF	CF80LP CF80DF
Engine Models Available	K21	K21	K21	K21/K25	K21/K25	K21/K25	K25	K25	K25	K25	K25
Load Capacity - lb	3000	3500	4000	4000	5000	5500	6000	6000	6500	7000	8000
Wheelbase - in	46.9	46.9	46.9	55.1	55.1	55.1	55.1	59.1	55.1	59.1	59.1
Overall Width - in	38.2	38.2	38.2	42.1	42.1	43.1	43.1	43.9	43.9	45.9	45.9
Overall Length (no forks) - in	81.9	83.1	84.4	89.0	91.3	93.9	95.3	96.5	96.3	98.2	100.0
Overall Height (OHG) - in	81.1	81.1	81.1	82.1	82.1	82.1	82.1	82.3	82.1	82.3	82.3
Turning Radius (outside) - in	68.3	69.5	70.9	76.0	78.3	79.5	80.7	80.9	81.5	82.5	83.9

## COMPACT PNEUMATIC TIRE (NOMAD) 3000 – 5000 LB. MODELS

SHORT MODEL CODES	AF30LP AF30DF	AF35LP AF35DF	AF50LP AF50DF
Engine Models Available	K21	K21	K21
Load Capacity - lb	3000	3500	5000
Wheelbase - in	50.8	50.8	59.1
Overall Width - in	40.7	40.7	46.3
Overall Length (no forks) - in	83.9	85	92.9
Overall Height (OHG) - in	83	82.7	82.3
Turning Radius (outside) - in	72.6	73.8	80.7

## ENGINES

ENGINE MODELS	K21 (2.1 LITER) GAS, LPG, DUAL FUEL	K25 (2.5 LITER) GAS, LPG, DUAL FUEL
Displacement - cu in	126	151.8
Rated Output - hp/rpm	55 / 2700	62.9 / 2700
Rated Torque - ft-lb/rpm	111.4 / 2000	138.7 / 1600

# Reliability.

It's the defining trait of our company and our forklifts.



UniCarriers' roots extend back over 100 years, and over that time, strong, reliable performance has always been the hallmark of our organization, our people and our equipment.

Today, our unrivaled reliability continues to provide UniCarriers' customers with a competitive edge. And together, we move the merchandise that moves world commerce with greater efficiency, economy and reliability.

When it comes to providing forklifts that make a difference for our customers and theirs...



## We Never Quit.

**UNICARRIERS**<sup>®</sup>  
[ **FORKLIFT** ]  
UniCarriersAmericas.com



SB-PLATINUM-II 07-2015 Printed in U.S.A.

UniCarriers<sup>®</sup> is a registered trademark of UniCarriers Corporation. Platinum II<sup>®</sup>, Nomad<sup>®</sup> and OptiView<sup>®</sup> are all registered trademarks of UniCarriers Americas. UniCarriers Americas Corporation reserves the right to make product changes relating to colors, equipment, specifications or available options without notice. For more information, contact your UniCarriers representative.



**Reliability.**

It's the defining trait of our company and our forklifts.



**Debris Resistance Package**  
 Includes a belly screen and slotted wheel well inserts to prevent larger debris from entering the engine compartment and affecting key components. For additional protection, select the Recycler Package.



**Blue LED Pedestrian Awareness Light**  
 Reverse driving actuates an optional blue spotlight to illuminate the floor, for advanced visual warning.



**Tilt Cylinder Protection**  
 Cylinder boots and covers provide extra protection against contaminants that can cause premature wear on cylinder packing.




**Extended Overhead Guard**  
 Extension provides protection to mounted components, including on-board computer and headlight (shown).



**Fingertip Controls**  
 Increase operator productivity with ergonomic hydraulic controls. Choose single joystick or multiple lever designs.



**Polycarbonate Overhead Guard Cover**  
 Prevents small debris from entering the operator compartment through the overhead guard.



**Sideshifting Fork Positioner**  
 Hydraulically positions forks, eliminating the need for manual adjustment by the operator, providing increased productivity.



**Rear LED Combination Lights**  
 Package includes a reflector, turn signals, brake and back-up lights. Design provides high visibility and vibration resistance for long life and low service costs. Choose vertical or horizontal mounting (shown).



**Radiator Screen**  
 Minimizes debris entering radiator, resulting in more efficient engine cooling.

UniCarriers' roots extend back over 100 years, and over that time, strong, reliable performance has always been the hallmark of our organization, our people and our equipment.

Today, our unrivaled reliability continues to provide UniCarriers' customers with a competitive edge. And together, we move the merchandise that moves world commerce with greater efficiency, economy and reliability.

When it comes to providing forklifts that make a difference for our customers and theirs...

**We Never Quit.**



**Engine Powered Forklifts**

**Gas, LP, Dual Fuel**  
**3,000 - 8,000 lbs. Capacities | Cushion Tire**  
**3,000 - 7,000 lbs. Capacities | Pneumatic Tire**



# Platinum II® Series Applications

Powered by our GTC K21 and K25 engines, the Platinum II sets the standard for performance, using less fuel and delivering more cycles per hour in a variety of demanding applications that include:

- Manufacturing
- Warehousing
- Recycling
- Beverage/Bottling
- Trucking



Look for these symbols for features available only on UniCarriers forklifts or that provide a proven performance advantage as compared to competitive trucks.



## NEVER QUIT.

It defines our forklifts and the company that builds them.

Over the course of a century, the company known as UniCarriers took shape. As we grew and evolved into a US manufacturer with a global reach in nearly 100 countries worldwide, much has changed, but one thing hasn't: our mission. UniCarriers is committed to providing you with the ultimate in reliability, performance, and value.

And that commitment can be seen in the Platinum II Series. Powered by our legendary K21 and K25 industrial engines, our rugged Platinum II forklifts deliver greater torque and horsepower...reduce CO, HC and NOx exhaust emissions...and come standard with some of the most advanced performance, security and operator comfort features available anywhere. Plus, it's all backed by the best standard, limited warranty in the business.



### Up Your UpTime

Discover reliability features that cut downtime and keep your business up and running



### Comfort Zone

Your drivers and your entire operation will benefit from our comfort & productivity features



### Power & Performance

You'll find amazing efficiency, reliability and performance in our K21 and K25 engines



### Sweet Savings

The Platinum II is designed to deliver you a low cost of ownership year after year after year



### Play It Safe

Safety is everybody's business, and the Platinum II is all business when it comes to safety



### Control Freak

You're in complete control when it comes to managing costs and productivity



### Versatility & Value

Discover how our unique design can help you improve performance indoors and out



### Make It Yours

Already well appointed, Platinum II can be customized to meet your specific needs



To learn more, and a find a dealer near you, visit [UniCarriersAmericas.com](http://UniCarriersAmericas.com)

# Up Your UpTime

Trained technicians can **program service interval alerts** for each unit in operation through the meter panel. Drivers are notified when scheduled maintenance is required.

When it comes to keeping your operation up and running, the Platinum II Series offers you significant advantages, beginning with a reliable cooling design, service reminders and longer maintenance intervals. Throughout the Platinum II you'll find innovative and proven protection and warning systems to help you maximize uptime, while minimizing cost.

## Longer Preventative Maintenance Intervals

With the Platinum II Series, most major service intervals are only required every 500-600 hours, reducing labor and lowering your operating costs.



A standard **parking brake transmission interlock** keeps the forklift in neutral and prevents the operator from driving while the parking brake is engaged to protect the brakes and transmission and reduce premature brake wear.




Inhibit operators from shifting at high speeds with our **SmoothShift** system. This option limits transmission shock and excessive wear— and extends service life too.




## Easy LP Tank Changes

With our simplified LP replacement system, an optional bracket swings out 90°, then pulls down to a manageable height, for faster, easier tank replacement. *Not available on all models.*



Keep your starter and battery healthy with a **starter interlock**. This optional equipment **protects the forklift's starting system** by restricting repeated attempts to start the engine when the LP system is out of fuel.



## Defend Against Overheating


Our reliable cooling system includes an electronic engine protection and warning system that **monitors radiator fluid and transmission oil temperatures at all times**. This system also contains a field-proven bottom bypass design with thermostat to **prevent hot spots and prolong engine life**. And its large 10-blade fan and aluminum radiator produce effective cross-flow cooling.

## Reduce Downtime through Self-Diagnostics

Integrated **on-board diagnostics** provides immediate truck status. Standard equipment on the Platinum II Series, this intuitive dialogue display, combined with accessible service history, **reduces troubleshooting time**, so the unit is back in operation faster. Everything is done through its smart LCD panel. No handset device is needed.



# Comfort Zone



## Superior Visibility

A standard high-visibility carriage\* and your choice of an OptiView®, triple stage or wide-view mast — together these features produce clear sightlines for both loading and moving.

*\*Available at no additional cost on model capacities up to 5500 lbs.*



## Improved Control and Security

Maneuverability during reverse driving is easier with an optional secure assist grip. And it helps keep the operator's hand inside the compartment where it belongs. A horn button is included.




## Convenience at Your Fingertips

Standard automotive-style controls are located on either side of the steering column for accessibility and intuitive operation.



## Get a Smoother Ride

Pneumatic tire models are designed with a floating powertrain that includes four independent dampers, to reduce vibrations that can cause operator fatigue.




## Our Seat Supports Your Driver and Your Productivity

The lumbar support and weight adjustments create customized comfort for the operator, while a non-cinching seatbelt allows a wider range of movement. The full suspension design absorbs shocks for a smoother, more comfortable ride — and it's all standard on Platinum II Series forklifts.

**Lumbar support adjustment**

**Weight adjustment**

*Seat and backrest cushions can be individually replaced for enhanced savings.*



## Better Fork Tip Visibility

Controls are ergonomically placed across a low profile cowl, making visibility while picking up loads easier for a variety of operator heights.

## Add a Spinner Knob for Easier Handling

Operators love this optional feature because it gives them even easier control behind the wheel.

# Power & Performance

## Operator Efficiency Achieved

Choose the optional integral side shifter resulting in fewer moves to store and retrieve loads, while minimizing capacity loss versus hang-on designs.



## More Power, More Efficiently

Advanced engine technology makes it possible for our K21 and K25 engines to deliver **greater torque at lower RPMs**. This is achieved due to a combination of factors, including **direct ignition coils connected to each cylinder**, a centrally positioned spark plug on the combustion chamber as well as electronic monitoring and control systems. Platinum II models also include an atmospheric sensor that delivers enhanced performance in high altitudes.



## Paired for Maximum Performance

Built to our specifications, the Platinum II's transmission is uniquely designed to **optimize the horsepower and torque of our K21 and K25 industrial engines**. This proven drivetrain delivers powerful, yet efficient performance.



## Cleaner Running Engines for Greater Performance

The injector valve's powerful opening force aids in conditions where lower quality LP fuel is used. Gas is located under the valve to **help reduce possible tar build up on the injectors** which can adversely affect performance. A pressure sensor is located between the two injectors.



## Consistent Performance through Reliable Technology

The Platinum II's engine and vehicle control modules along with multi-function display communicate through a reliable CAN-bus network to manage changing system requirements and maintain consistent performance.



## Built for Rugged Dependability

Solid steer axles and thick steel front fenders provide protection against harsh work environments.




## Compact Design

A small steering wheel and intuitive controls make these trucks highly suited for maneuverable performance within confined areas of the warehouse.




The Nomad's standard Power setting allows you to achieve maximum performance — and an annual productivity increase of up to 2500 cycles per truck.

*Study findings are based on a 1200-hour usage*



Switch to the Platinum II's optional Economy mode to get greater fuel efficiency. Independent testing has shown our K21 engines use nearly 11% less fuel compared to competitive models under unloaded conditions.\*

\* Results based on 5000 lb. capacity LP cushion tire models in Economy mode.



# Sweet Savings



## Extra Protection Without Extra Expense




In the event of excessive heat or loss in engine oil pressure, our **Powertrain Protection System** reduces engine RPM for longer engine and drivetrain life. This great feature is standard on models powered by our K21 and K25 engines, versus competitive forklifts requiring a costly add-on.

## Reduce Tire Wear & Save Fuel



Our power/economy controlled acceleration feature restricts the acceleration rate to **maximize fuel economy and minimize tire spin**. Gradual acceleration is also **useful when moving fragile loads or operating in confined areas**. Three design choices for this option offer increasingly more **security against tampering**: toggle switch, key switch or set internal parameters to keep this feature activated.



## Extended Service Intervals

The electronic ignition system means you'll service the Platinum II less often because the recommended times between routine maintenance is longer. And you'll spend less time doing it because the critical service points — including fluids, filters and belts — are all readily accessible.

## Eliminate Spark Plug Wires and Timing Adjustments

The engine cylinder timing is individually controlled through an ignition coil at each plug, eliminating associated maintenance. Free from mechanical linkages or aging wires that can cause performance loss, this design delivers better engine efficiency.

## Other serviceability features:

- Easy oil filter replacement
- Fast fan belt adjustment
- Accessible radiator



## Long Life LEDs

Everything about the Platinum II is designed for longer life and greater savings, including the standard LED headlights that deliver greater visibility while being more economical and cost-effective over the life of the machine.

## Repositionable Headlights



## Save More, Waste Less



With the Platinum II's **standard LPM<sub>ax</sub> System** nearly every drop of liquid LP is used thanks to its reliable and timely low fuel warning, **reducing early tank replacement and saving you money**. An average 8-minute\* warning means the operator can maximize productivity — instead of lugging an empty tank to the refill station.



## Our Overhead Guard Reduces Your Overhead

Beyond ample headroom, the five-piece overhead guard takes **75% less time to make needed replacements** versus competitors' single-piece, welded-on guards. That cuts downtime and costs.

\*Based on typical traveling operation in unloaded condition. Time interval varies depending upon individual application and usage.

# Play It Safe

As a leader in clean air engines for nearly a decade, our products have benefited from the knowledge gained through our automotive heritage. Our K21 and K25 industrial engines incorporate an electronic engine control system, using a closed loop design to produce high combustion efficiency with lower and cleaner emission levels. We've also included several security systems as standard, and more options to meet your particular needs.



## For Even Greater Security

Several options are available for added protection:

- **Seatbelt Interlocks** include a variety of choices for restricting forklift operations if the seatbelt is not latched.
- **Fire Extinguisher** mounted to the overhead guard pillar, for quick and easy access.
- **Orange Seatbelt** is highly visible, making seatbelt usage easier to enforce.
- **LP Safety Rating** is UL approved.

## Operator Presence System



This comprehensive system includes a **seat-actuated power interrupt with mast-lock**, automatically preventing lift and tilt operations if the operator leaves the seat. The **return-to-neutral** feature minimizes forklift movement if the operator leaves the truck while still in gear. Other audible and visual warnings come standard, including **parking brake warning** and **seatbelt alarm**.




A rubber damper provides enhanced stability and easier handling



## Safety Doesn't Have to be Complicated

Unlike the complex systems offered by some competitors, our cushioned stability control is simple, extremely effective and **zero maintenance** — enhanced lateral stability is achieved by a rubber damper placed between the axle and frame.



## Seeing is Believing

Cylinders are positioned behind the mast rails resulting in fewer visual obstructions for the operator. Ideal for facilities that transport delicate loads, our optional OptiView® mast makes fork positioning and load handling easier.




OSHA strictly regulates carbon monoxide (CO) levels in the workplace for good reason.



The Platinum II's CO levels are among the lowest in its engine class — three times lower than those of a major competitor based on 2015 certification results from the California Air Resources Board.

We achieved these lower and cleaner emission levels through the higher combustion efficiency delivered by our electronic engine control system that incorporates a Vehicle Control Module (VCM), Engine Control Module (ECM) and a 3-way catalytic muffler.



\*Based on 2015 CARB certification results.

# Control Freak

## Make a Positive Impact

A variety of optional impact sensors are available to record each time the forklift comes into contact with a stationary object, allowing you to respond accordingly.

### Single Handle Control Lever

Faster, easier and more fluid, our single handle control combines both lift and tilt functions for greater productivity. It's standard equipment on the Platinum II Series — and not available from any other forklift brand. Separate control levers are available at no charge.



### Auto-Tilt Leveling System

Press the button on the hydraulic control lever to tilt the forks forward to a horizontal position. This option is used for easier load placement and retrieval operations.



### Parking Brake Alarm

As part of the Operator Presence System, a warning buzzer alerts the driver if he leaves the seat without first setting the parking brake.

### Forward Thinking ..... Back-Up Alarm


Our standard back-up alarm provides plenty of notice to pedestrians and other drivers in the area. For applications with varying noise levels, there is an optional self-adjusting alarm that adjusts sound volume based on ambient noise levels.



### Find Your Top Travel Speed Easier



With an optional speed switch, drivers can toggle from a high speed pre-set in one area then select a low speed, confident they are adhering to corporate requirements\*.



Select the security key switch option to lock in a pre-set high or low speed\*.


### Set Travel Speeds Without Losing Productivity

Top travel speed is electronically controlled, so you won't sacrifice lift performance. The great news? No tools are needed to set desired speeds\*.

\* Speed pre-sets performed by trained service technician

### The Ultimate in Control

The interactive meter panel on the Platinum II Series provides operators and technicians with a wealth of information through its LCD warnings and readouts. A visual indicator for its return-to-neutral feature shows the forklift's transmission direction.



Our multi-function display provides an at-a-glance view of critical functions:

- A** Multipurpose warning
- B** Check engine warning
- C** Oil pressure warning
- D** Charge warning
- E** Parking brake warning
- F** Seatbelt warning
- G** Directional indicator
- H** Fuel & water temperature gauges
- I** Multi-function display:
  - Hour meter
  - Clock/calendar
  - Speedometer
  - Programmable service reminder
  - Error codes



# Versatility and Value

# The Nomad Series



Don't downsize your fleet – right size it. A proven performer across a variety of applications, the Nomad is bound to be one of the most relied upon forklifts in your facility. From loading dock to work yard, you'll discover the many ways these flexible trucks will benefit your operation.



\*Calculations based on comparison of Nomad vs. pneumatic tire forklift of same capacity.

## Two Forklifts in One

The Nomad Series is a UniCarriers exclusive. At home anywhere, its cushion tire-sized chassis rides on solid pneumatic tires to deliver exceptional performance both indoors and out. And because our Nomad is part of the Platinum II family, you'll also enjoy the same reliability that comes with utilizing UniCarriers brand equipment in your operation.

## For Indoor and Outdoor Use

The Nomad Series is available in 3000, 3500 and 5000 lb. lifting capacities. Its short wheelbase and tight turning radius mean it's sized like a standard cushion tire forklift, offering precise maneuverability in confined areas. But don't let its size fool you. It's just as effective in tough outdoor applications. And it offers higher capacity retention versus comparable pneumatic tire trucks.

Operate on improved surfaces for best outdoor performance results.



Get up to 8% tighter turning radius without sacrificing capacity.\*

**72.6-87.5**  
INCHES

# Make It Yours

Choose from a variety of options to customize your ride. If you don't see what you need, contact your authorized UniCarriers dealer for help.



Strobe & LED Work Lights

Trucker's Mast

High Air Intake Pre-Cleaner

Overhead Guard-Mounted Fire Extinguisher

Forks with High Visibility Paint

Dual Drive Tires\*

\* Available on pneumatic tire models only. Standard, pre-drilled holes in thick front fenders simplify field installation of dual tire option. Data plate change is required. Consult factory.

## Option Availability

	LP	GASOLINE	DUAL FUEL
<b>VEHICLE MANAGEMENT</b>			
Vehicle Control Module (VCM)	●	●	●
Operator security PIN access	●	●	●
Interactive LCD meter panel	●	●	●
On-board diagnostics and programmable service reminders	●	●	●
Engine coolant temperature gauge	●	●	●
Oil pressure, transmission fluid and low coolant warning lights	●	●	●
LPMax low fuel warning	●	—	●
Fuel gauge - gas	—	●	●
SmoothShift system	○	○	○
Starter interlock - low LP	○	—	○
<b>POWERTRAIN</b>			
Electronic Engine Control System	●	●	●
Engine/transmission protection and warning system	●	●	●
Floating powertrain for reduced vibration (pneumatic)	●	●	●
Three-way catalytic converter	●	●	●
Cushioned stability control	●	●	●
Travel speed control (high/low speed selector)	○	○	○
Controlled acceleration (power/economy selector)	○	○	○
Radiator screen	○	○	○
Diffusion exhaust muffler	○	○	○
<b>LP SYSTEM</b>			
Swing-out LP bracket*	●	—	●
Swing-down LP bracket*	○	—	○
<b>BRAKE</b>			
Parking brake with warning buzzer	●	●	●
Parking brake transmission interlock	●	●	●
<b>MAST</b>			
Seat actuated auto-mast lock system	●	●	●
OptiView® three-stage mast	○	○	○
High-Visibility Carriage*	●	●	●
<b>HYDRAULIC SYSTEM</b>			
Single lift/tilt control lever	●	●	●
Separate lift & tilt control levers	○	○	○
Automatic fork leveling*	○	○	○
<b>OPERATOR CONVENIENCES</b>			
Full suspension seat with weight & lumbar adjustment	●	●	●
Overhead guard-mounted LED headlights	●	●	●
Rearview mirrors	○	○	○
Rear LED combination light package (turn, stop, back-up)	○	○	○
Rear LED drive light	○	○	○
Secure rear grip with horn button	○	○	○
<b>PROTECTION /SECURITY</b>			
Operator Presence System with return-to-neutral and auto mast lock	●	●	●
Seatbelt interlocks	○	○	○
UL Safety rating*	○	—	—
Back-up warning alarm	●	●	●
Self-adjusting back up alarm	○	○	○
Fire Extinguisher	○	○	○

\*Available on select models. Consult factory.

## Specifications

Safety ratings available on select models/fuel types

### PNEUMATIC TIRE 3000 – 7000 LB. MODELS

SHORT MODEL CODES	PF30 PF30LP PF30DF	PF35 PF35LP PF35DF	PFS40 PF40LP PFS40DF	PF(U)40 PF(U)40LP PF(U)40DF	PF(U)50 PF(U)50LP PF(U)50DF	PF55 PF55LP PF55DF	PF60 PF60LP PF60DF	PF70 PF70LP PF70DF
Engine Models Available	K21	K21	K21	K21/K25	K21/K25	K25	K25	K25
Load Capacity - lb	3000	3500	4000	4000	5000	5500	6000	7000
Wheelbase - in	55.1	55.1	55.1	63.0	63.0	63.8	66.9	66.9
Overall Width - in	41.9	41.9	41.9	45.3	45.3	49.2	49.2	50.4
Overall Length (no forks) - in	89.0	90.2	91.3	96.9	99.0	102.8	105.5	108.5
Overall Height (OHG) - in	83.3	83.3	83.3	83.5	83.5	84.6	84.6	84.8
Turning Radius (outside) - in	76.2	77.6	79.1	83.5	85.8	88.2	90.6	94.1

### CUSHION TIRE 3000 – 8000 LB. MODELS

SHORT MODEL CODES	CF30LP CF30DF	CF35LP CF35DF	CFS40LP CFS40DF	CF(U)40LP CF(U)40DF	CF50 CF(U)50LP CF(U)50DF	CF55 CF(U)55LP CF(U)55DF	CFS60LP CFS60DF	CF60LP CF60DF	CFS65LP CFS65DF	CF70LP CF70DF	CF80LP CF80DF
Engine Models Available	K21	K21	K21	K21/K25	K21/K25	K21/K25	K25	K25	K25	K25	K25
Load Capacity - lb	3000	3500	4000	4000	5000	5500	6000	6000	6500	7000	8000
Wheelbase - in	46.9	46.9	46.9	55.1	55.1	55.1	55.1	59.1	55.1	59.1	59.1
Overall Width - in	38.2	38.2	38.2	42.1	42.1	43.1	43.1	43.9	43.9	45.9	45.9
Overall Length (no forks) - in	81.9	83.1	84.4	89.0	91.3	93.9	95.3	96.5	96.3	98.2	100.0
Overall Height (OHG) - in	81.1	81.1	81.1	82.1	82.1	82.1	82.1	82.3	82.1	82.3	82.3
Turning Radius (outside) - in	68.3	69.5	70.9	76.0	78.3	79.5	80.7	80.9	81.5	82.5	83.9

### COMPACT PNEUMATIC TIRE (NOMAD) 3000 – 5000 LB. MODELS

SHORT MODEL CODES	AF30LP AF30DF	AF35LP AF35DF	AF50LP AF50DF
Engine Models Available	K21	K21	K21
Load Capacity - lb	3000	3500	5000
Wheelbase - in	50.8	50.8	59.1
Overall Width - in	40.7	40.7	46.3
Overall Length (no forks) - in	83.9	85	92.9
Overall Height (OHG) - in	83	82.7	82.3
Turning Radius (outside) - in	72.6	73.8	80.7

### ENGINES

ENGINE MODELS	K21 (2.1 LITER) GAS, LPG, DUAL FUEL	K25 (2.5 LITER) GAS, LPG, DUAL FUEL
Displacement - cu in	126	151.8
Rated Output - hp/rpm	55 / 2700	62.9 / 2700
Rated Torque - ft-lb/rpm	111.4 / 2000	138.7 / 1600